



Lumago palletbreaker
Python series



Thank you

Many thanks for your interest in our machines!

If you're looking to breakdown e.g. your full-sized wooden (1-way) pallets, boards, beams, boxes etc in a safe and effective way, the "PYTHON" series is an ideal solution.



Advantages:

- "large" input hopper (1300 mm or 1600 mm) "small" price
- Mobile, easy to carry
- Volume reduction up to 70%
- Clean warehouse / grounds / yard
- Significant savings in disposal costs (transport)
- Address pallet storage issues (insurance: 10 metres from building))
- Generate revenue instead of disposal costs
- From 7.5 kW installed power
- Easy handling

Please consider the environment

Lumago is proud to offer its customers a product that contributes to the "conscious sustainable entrepreneurship" and reduction of CO2 emissions.



Python series 1300 and 1600

The breaker screw, fitted with robust bearings, breakdown all kinds of wood waste.
The machine is suitable for whole / or part wooden pallets, crates, boards, planks etc. breaking them down into hand size pieces.
The (complete) pallets / wooden parts are loaded in the top of the machine.
The processing is one or more at a time.
The discharge opening is positioned bottom side underneath the bearing.

Processing capacity up to 50* pcs per hour

(*dependent on the material)

The machine operation is fully automatic and is equipped with safety switch and emergency shut-off. In the event of machine overload or blockage within the cutting chamber, the machine will auto-reverse to clear the issue and will restart automatically. After 5 unsuccessful attempts, within e.g. 2 minutes, the machine switch off. In addition, the machine switch-off automatically after 2 minutes in idling. A selector switch for automatic operation of the discharge conveyor (option) is available.



Technical

Technical information Type 1300 (Type 1600)

- Drive with gear motor 7.5 kW (11 KW), 400 V 50 Hz
- Equipped with approx. 5 m electric cable with CE plug
- Hopper opening 1300 mm (1600 mm) x 700 mm
- Main dimensions L 2100 (2400) x W 850 x H 1580 mm
- Discharge opening approx. 400x 100 mm
- Discharge height approx. 400 mm
- Electrical control box withl, main switch, selector switch, on / off switch and emergency stop
- Easy movable with forklift or otherwise
- Weight approx. 1100 kg
- Machine manual: English
- Coating in RAL 3002 and RAL 7022
- (technical changes reserved)
- CE certified and “Made in Holland”



Terms of delivery

Terms of delivery

The general terms of delivery and payment of Lumago Machinery b.v., apply exclusively to all deliveries and services, unless otherwise agreed in writing.

The conditions can be viewed and/or download on our homepage:

<https://www.lumago.nl>



Download the General Terms and Conditions of Lumago Machinery b.v. here

Contact

Contact

Lumago Machinery B.V.
Theo Lubbers
+31 547275062

www.lumago.nl
info@lumago.nl

Adress:

Dammaten 18-5
7472 DJ Goor

Postadress:

Paulus Potterstraat 22
7471 XJ Goor
The Netherlands



“Feel free to contact us!”